

PACO SD-AM-Qualities for SD-Meshes PACO High-Tech-Screens

No. of Mesh	PACO-Code	Opening		Wire Diameter		Open Area (%)	Weight (g/m ²)	Thickness (µm)	Theor. Ink.-vol. (Cm ³ /m ²)	Recom. Tension (N/cm)
		(µm)	(inches)	(mm)	(inches)					
230	SD-AM 30/80	80	.0031	0,030	.0012	52,8	115	60-62	33,0	26-36
270	SD-AM 36/59	59	.0023	0,035	.0014	39,0	180	72-74	29,0	36-46
300	SD-AM 30/55	55	.0022	0,030	.0012	38,0	140	61-63	26,5	34-44
325	SD-AM 29/50	50	.0020	0,029	.0011	41,0	131	60-62	25,4	38-48
355	SD-AM 32/40	40	.0016	0,032	.0012	31,0	170	64-66	20,5	38-48
370	SD-AM 26/43	43	.0017	0,026	.0010	39,0	130	53-55	22,1	30-40
400	SD-AM 23/40	40	.0016	0,023	.0009	31,3	110	45-47	19,5	28-38
400	SD-AM 25/38	38	.0015	0,025	.0010	37,0	130	52-55	19,5	32-42